

HDMI CABLES

GL-PR-H15MM-4K



HDMI 1.4
HIGH DEFINITION MULTIMEDIA INTERFACE

4K **10.2 Gbps**

HDCP 2.2

3D **EDID**

Specification

Model Number	GL-PR-H15MM-4K
Description	GRAND LOGIC HDMI 15 m Male to Male - 4K
Resolution & Refresh Rate	3840 x 2160 @30Hz
Frame Rate	24, 25, 30
Chroma Sampling	4:4:4
Color Bit Depth	8 and 12 bits per color
Max. Video Data Rate	10.2 Gbps
Ethernet Channel	Compatible
Signal Transmission	Unidirectional
Marking	SOURCE & DISPLAY
Performance	
Resolution Range	Up to 4K @30Hz (3840 x 2160), FHD @60 Hz (1920 x 1080) 8 bit color depth, max. 10.2 Gbps data rate
Voltage	30 V
Conductor Resistance	400Ω/km
HDMI	V 1.4
HDCP	2.2
EDID	Compatible
CEC	Compatible
Audio Return Channel	Compatible
3D	Compatible @1080P
Max. LPCM Audio Channels	32
Max. Audio Sampling Rate	24 bits

HDMI CABLES

GL-PR-H15MM-4K

General - Physical Parameters	
Connector Type	Male Type A HDMI to Male Type A HDMI
Contacts	Gold Flash
Material	Conductors : 7/Φ0.12 mm Tinned Copper Drain Wire : 7/Φ0.1 mm Tinned Copper Shielding : 16x4/Φ0.12 mm Aluminium-magnesium Jacket: PVC
Connector Dimensions	Length (L): 36 mm Width (W): 18 mm Thickness (T): 10.5 mm
Cable Outer Diameter (mm)	7.3 mm
Cable Length	15 m (49 ft.)
Temperature Rating	80 °C
Colour	Space Grey
AWG	28

