

AUDIO, SPEAKER & 5MHR VGA CABLES**Specification****Speaker Cable : GL-2CS100**

Description	16 AWG(65/34 AWG), bare copper conductor, PVC insulated, 2 conductor laid, PVC jacketed Speaker Cable
Conductor	Annealed bare Copper Conductor EC Grade IS:8130
Number of Wires	65 Nos
Overall Diameter (nominal)	2.6
Material	PVC
Diameter	6.50 mm (Nom)
Outer Sheath Colour	Dark Grey

Audio Cable : GL-2CSA100

Description	20 AWG (10/30 AWG), tinned copper conductor, PVC insulated, 2 conductor cabled Screened with Aluminium mylar tape with tinned copper drain wire(10x30 AWG), PVC jacketed Audio Cable
Conductor	Annealed bare Copper Conductor EC Grade IS:8130
Number of Wires	10 Nos
Overall Diameter (nominal)	1.8
Material	PVC
Diameter	5.50 mm (Max)
Outer Sheath Colour	Dark Grey

5MHR VGA Cables : GL-VA100

Conductor	7/0.16 TC
Insulation	FPE Ø1.8
Jacket	PVC
Filling	Fiber
Color	Grey
Outer Diameter	9.0 mm

MODEL DESCRIPTION

GL-2CSA100	Professional 2-Core Shielded Audio Cable 100 m 20 AWG
GL-2CS100	Professional 2-Core Speaker Cable 100 m 16 AWG
GL-VA100	Professional 5 MHR VGA Cable 100 m